

Specifications

- Door sections are formed from heavy, 25-gauge galvanized draw quality steel
- Section joints are roll-formed into a tongue-and-groove design which produces a superior weather seal
- Inside stiles are made of galvanized steel and stile holes are "dimpled" for increased holding power
- Bottom weather seal utilizes an aluminum retainer and extruded virgin vinyl
- Extra heavy paint system¹ in your choice of white, almond, desert tan, sandstone or brown
- R-values⁵:
1-3/8" Insulated Models - 7.94
9/16" Insulated Models - 3.56

Color Selections³



PANEL CONSTRUCTION



(A) Utilizes a 1-3/8" thick CFC⁴ free polystyrene insulation



(B) Utilizes a 9/16" thick CFC⁴ free polystyrene insulation with vinyl back cover

Each model utilizes a tab-loc system that holds the steel end and intermediate stiles firmly in place, creating increased strength and rigidity.


FLIER NUMBER_OEM2250-0708R4

WINDOW & GLASS OPTIONS

Add a touch of elegance and complement the outside of your home with the addition of decorative and designer glass options. These options are an investment designed to improve the natural beauty of the exterior while adding to the value of your home.

Standard Window Design Trims

SHORT PANEL



2-4 Piece Sunburst



8 Piece Sunburst



7 Piece Sunburst



6 Piece Sunburst




5 Piece Sunburst



Cathedral



Sherwood




Stockton



Cascade




Mission



Waterton

LONG PANEL



2-2 Piece Sunburst



4 Piece Sunburst



3 Piece Sunburst



Sherwood



Stockton




2-2 Piece Arched Stockton



4 Piece Arched Stockton



Madison



2-2 Arched Madison



4 Piece Arched Madison



Cascade



Mission



Waterton

Designer Lites²



Plain DSB or Poly

Tinted

Obscure

All information presented is based on the specifications and features available at the time of printing and is subject to change without notice.

SECTIONS MANUFACTURED BY:



These door models utilize sections manufactured in Arthur, Illinois USA and warranted by C.H.I. Overhead Doors.

Footnotes

1. Extra heavy paint system consists of .25 mil. primer with rust inhibitor and a .75 mil. coating of baked-on polyester paint. 2. All designer lights are either transparent or semi-transparent. For all available window options, please see our Glass Option Brochure. 3. Refer to samples at your local garage door professional for exact color match. 4. Chlorofluorocarbon (CFC) free. 5. R-value testing is in accordance with ASTM C518 standards.

